

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

ACTi



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
ACD2000Q	A4Q-220-V3.02.04-AC	MPEG4 M-JPEG	4	720x480	2-way	2/2	Yes	-	-	
ACD2100	A1D-220-V3.08.08-AC	MPEG4 M-JPEG	1	720x480	2-way	2/2	Yes	-	-	
ACD2200	A4D-R2N-V2.05.02-AC	MPEG4 M-JPEG	4	720x480	2-way	8/8	Yes	-	-	
ACD2300		MPEG4 M-JPEG	8	720x480	2-way	16/16	Yes	-	-	Supported by design
ACD2400	AGD-R2N-V2.05.02-AC	MPEG4 M-JPEG	16	720x480	2-way	32/32	Yes	-	-	
ACM1011	A1D-220-V3.10.22-AC	MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	
ACM1231		MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	Supported by design
ACM1232		MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	Supported by design
ACM1311		MPEG4 M-JPEG	1	720x480	2-way	-	-	-	-	Supported by design
ACM1431		MPEG4 M-JPEG	1	720x480	2-way	-	-	-	-	Supported by design
ACM1432		MPEG4 M-JPEG	1	720x480	2-way	-	-	-	-	Supported by design
ACM1511	A1D-220-V3.11.13-AC	MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	
ACM3001		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	-	Supported by design
ACM3011		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	-	Supported by design
ACM3211		MPEG4 M-JPEG	1	720x480	2-way	-	Yes	-	-	Supported by design
ACM3311		MPEG4 M-JPEG	1	720x480	2-way	-	Yes	-	-	Supported by design
ACM3401	A1D-220-V3.10.22-AC	MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	
ACM3411		MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	Supported by design
ACM3511		MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

ACTi



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
ACM4000		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	-	Supported by design
ACM4100	A1D-220-V3.09.14-AC	MPEG4 M-JPEG	1	640x480	2-way	-	-	-	-	
ACM4200	A1D-220-V3.11.13-AC	MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	
ACM4201		MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	Supported by design
ACM5001		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	-	Supported by design
ACM5601	A1D-220-V3.08.08-AC	MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	-	
ACM5611		MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	-	Supported by design
ACM5711	A1D-220-V3.08.08-AC	MPEG4 M-JPEG	1	720x480	2-way	1/1	-	-	-	
ACM7411	A1D-220-V3.09.14-AC	MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	-	
Note:	A1D-220-V3.09.14-AC: There is problem at 160x112 resolutions.									
ACM8201	A1D-220-V3.10.22-AC	MPEG4 M-JPEG	1	1280x1024	2-way	1/1	Yes	-	-	
Note:	A1D-220-V3.09.14-AC: There is problem at 160x112 resolutions.									
ACM8211	A1D-220-V3.09.14-AC	MPEG4 M-JPEG	1	1280x1024	2-way	1/1	Yes	Yes	-	
ACM8511	A1D-220-V3.11.13-AC	MPEG4 M-JPEG	1			1/1	Yes	Yes	-	
CAM5130		MPEG4	1	720x480	-	1/1	Yes	Yes	-	Supported by design
CAM5140		MPEG4	1	720x480	-	1/1	Yes	Yes	-	Supported by design
CAM5150		MPEG4	1	720x480	-	1/1	Yes	Yes	-	Supported by design
CAM5200		MPEG4	1	720x480	-	1/1	-	Yes	-	Supported by design
CAM5201		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

ACTi



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
CAM5221	A1D-M2N-V2.08.11-AC	MPEG4	1	720x480	1-way	1/1	-	Yes	-	
CAM5300		MPEG4	1	720x480	-	1/1	-	Yes	-	Supported by design
CAM5301		MPEG4	1	720x480	-	1/1	-	Yes	-	Supported by design
CAM5321		MPEG4	1	720x480	-	1/1	-	Yes	-	Supported by design
CAM5500		MPEG4	1	720x480	-	1/1	-	Yes	-	Supported by design
CAM6100		MPEG4	1	720x480	2/2	-	Yes	Yes	-	
CAM6200	A1D-2.07.14-AC	MPEG4	1	720x480	-	2/2	Yes	Yes	-	Supported by design
CAM6220	A1D-2.07.14-AC	MPEG4	1	720x480	-	2/2	Yes	Yes	-	Supported by design
CAM6500		MPEG4	1	720x480	2-way	2/2	Yes	Yes	-	Supported by design
CAM6510	A1D-M2N-V2.08.11-AC	MPEG4	1	720x480	2-way	2/2	Yes	Yes	-	
CAM6520		MPEG4	1	720x480	2-way	2/2	Yes	Yes	-	Supported by design
CAM6600		MPEG4	1	720x480	2-way	2/2	Yes	Yes	-	Supported by design
CAM6610		MPEG4	1	720x480	2-way	2/2	Yes	Yes	-	Supported by design
CAM6620		MPEG4	1	720x480	2-way	2/2	Yes	Yes	-	Supported by design
CAM6630		MPEG4	1	720x480	2-way	2/2	Yes	Yes	-	Supported by design
CAM7100		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Supported by design
CAM7120		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Supported by design
CAM7200		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Supported by design
CAM7220		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

ACTi



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
CAM7300		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Supported by design
CAM7301		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Supported by design
CAM7320		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Supported by design
CAM7321		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Supported by design
CAM7322		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Supported by design
SED2100		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Supported by design
SED2120	A1D-M2N-V2.08.11-AC	MPEG4	1	720x480	-	2/2	Yes	Yes	-	
SED2140		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Supported by design
SED2310Q		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Supported by design
SED2320Q		MPEG4 M-JPEG	1	720x480	1-way	2/2	Yes	Yes	-	Supported by design
SED2400		MPEG4	2	720x480	1-way	2/2	Yes	Yes	-	Supported by design
SED2420	A1D-220-V3.08.08-AC	MPEG4	2	720x480	1-way	-	-	Yes	-	
SED2600		MPEG4	8	720x480	1-way	16/16	Yes	Yes	-	Supported by design
SED2610		MPEG4	8	720x480	1-way	16/16	Yes	Yes	-	Supported by design
SEM1110		Mpeg4	1	720x480	1-way	-	-	Yes	-	Supported by design
TCM4301	A1D-310-V4.05.13-AC	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Supported by design
TCM5311	A1D-310-V4.05.13-AC	H.264 MPEG4 M-JPEG	1	1280x960	1-way	1/1	-	Yes	-	
AMU-9401	A1D-220-V3.10.22-NB	MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	
AMU-9711	A1D-220-V3.10.22-NB	MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

ACTi



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
TMU-9811	A1D-310-V4.07.10-NB	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	-	
TMU-9911	A1D-310-V4.07.10-NB	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	-	
TCM5312		H.264 MPEG4 M-JPEG	1	1280x960	2-way	1/1	-	-	Yes	Supported by design
TCM5601	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	
TCM5611		H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	Supported by design
TCM7411		H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	Supported by design
TCM3511	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	
TCM1511	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	
TCM1231	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	
TCM1232		H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	Supported by design
TCM4101		H.264 MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
TCD2500	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	720x480	2-way	2/1	-	-	Yes	
ACM4001		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	-	Supported by design
ACM3601	A1D-220-V3.10.22-AC	MPEG4 M-JPEG	1	640x480	-	-	-	-	-	
ACM3603		MPEG4 M-JPEG	1	640x480	-	-	-	-	-	Supported by design
ACM3701	A1D-220-V3.10.22-AC	MPEG4 M-JPEG	1	1280x1024	-	-	-	-	-	
ACM3703	A1D-220-V3.10.22-AC	MPEG4 M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
Note:	ACD / ACM series cameras do not support FW 3.11.11.									
Note:	Only two I/O are shown on the interface as adding one channel on devices with I/O function.									

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Arecont										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
AV1300	64328	M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
AV1305	64331	H.264 M-JPEG	1	1280x1024	-	1/1	-	-	-	
AV1310		M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
AV1355	65130	H.264 M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
AV2000	64328	M-JPEG	1	1600x1184	-	-	-	-	-	Supported by design
AV2100	64328	M-JPEG	1	1600x1184	-	-	-	-	-	Supported by design
AV2105	64331	H.264 M-JPEG	1	1600x1184	-	1/1	-	-	-	
AV2110		M-JPEG	1	1600x1200	-	-	-	-	-	Supported by design
AV2155	64803	H.264 M-JPEG	1	1600x1184	-	-	-	-	-	
AV3100	64328	M-JPEG	1	2048x1536	-	-	-	-	-	Supported by design
AV3105	64331	H.264 M-JPEG	1	1920x1216	-	1/1	-	-	-	
AV3110		M-JPEG	1	2048x1536	-	-	-	-	-	Supported by design
AV3130	61906	M-JPEG	1	2048x1536	-	-	-	-	-	Supported by design
AV3135	65135	H.264 M-JPEG	1	2048x1536	-	1/1	-	-	-	
AV3155	65113	H.264 M-JPEG	1	2048x1536	-	-	-	-	-	
AV5100	61906	M-JPEG	1	2560x1600	-	-	-	-	-	
AV5105	64331	H.264 M-JPEG	1	2560x1600	-	1/1	-	-	-	
AV5110		M-JPEG	1	2560x1920	-	-	-	-	-	Supported by design
AV5155	65113	H.264 M-JPEG	1	2560x1600	-	-	-	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Arecont




Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
AV8180	65010	M-JPEG	4	1600x1184	-	-	-	-	-	Supported by design
AV8185	65026	H.264 M-JPEG	4	1600x1200	-	-	-	-	-	
AV8360	65010	M-JPEG	4	1600x1184	-	-	-	-	-	Supported by design
AV8365	65026	H.264 M-JPEG	4	1600x1184	-	-	-	-	-	Supported by design
AV10005M	65147	H.264 M-JPEG	1	3648x2752	-	-	-	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List


V 1.4.0 (2010.08.09)

ATLANTIS										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
A02-OIPCAM1		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
A02-OIPCAM2		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-OIPCAM3		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM5		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
A02-IPCAM6		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
A02-IPCAM7		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM8		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM9		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM10		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM11		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM12		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM13		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM14		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM15		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM16		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
A02-IPCAM17		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

AXIS										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
205		M-JPEG	1	640x480	-	-	-	-	-	Supported by design
206		M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
206M		M-JPEG	1	1280x1024	-	-	-	-	Yes	Supported by design
206W		M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
207	4.4	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	-	Yes	
207MW		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	-	Yes	Supported by design
207W		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	-	Yes	Supported by design
209FD		MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
209FD-R		MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
209MFD		MPEG4 M-JPEG	1	1280x1024	-	-	Yes	-	Yes	Supported by design
209MFD-R		MPEG4 M-JPEG	1	1280x1024	-	-	Yes	-	Yes	Supported by design
210		MPEG4 M-JPEG	1	640x480	-	1/1		-	Yes	Supported by design
210A	4.4	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
211		MPEG4 M-JPEG	1	640x480	-	1/1	-	-	Yes	Supported by design
211A		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
211M		MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	Supported by design
211W		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
212		MPEG4 M-JPEG	1	640x480	2-way	1/1	Yes	-	Yes	Supported by design
213		MPEG4 M-JPEG	1	704x576	2-way	2/3	Yes	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

AXIS										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
214	4.33	MPEG4 M-JPEG	1	704x480	2-way	1/1	Yes	-	Yes	
215		MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	Supported by design
216FD		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
216FD-V		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
216MFD		MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	Supported by design
216MFD-V		MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	Supported by design
221		MPEG4 M-JPEG	1	640x480	-	2/1	-	-	Yes	Supported by design
223M		MPEG4 M-JPEG	1	1600x1200	2-way	2/1	-	-	Yes	Supported by design
225FD		MPEG4 M-JPEG	1	640x480	-	2/1	-	-	Yes	Supported by design
231D		MPEG4 M-JPEG	1	704x576	-	4/4	Yes	-	Yes	Supported by design
231D+		MPEG4 M-JPEG	1	704x576	-	4/4	Yes	-	Yes	Supported by design
232D		MPEG4 M-JPEG	1	704x576	-	4/4	Yes	-	Yes	Supported by design
232D+		MPEG4 M-JPEG	1	704x576	-	4/4	Yes	-	Yes	Supported by design
233D		MPEG4 M-JPEG	1	704x576	2-way	4/4	Yes	-	Yes	Supported by design
240Q		M-JEPG	4	704x576	-	4/4	-	-	Yes	Supported by design
2400		M-JEPG	4		-	4/1		-	Yes	Supported by design
241Q		MPEG4 M-JPEG	4	704x576	-	4/4	-	-	Yes	Supported by design
241QA	4.3	MPEG4 M-JPEG	4	704x576	1-way	4/4	-	-	Yes	
241S		MPEG4 M-JPEG	1	704x576	-	4/4	-	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List


V 1.4.0 (2010.08.09)

AXIS										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
241SA		MPEG4 M-JPEG	1	704x576	1-way	4/4	-	-	Yes	Supported by design
242S		MPEG4 M-JPEG	1	704x576	-	4/4	-	-	Yes	Supported by design
243Q		MPEG4 M-JPEG	1	704x576	-	4/1	-	-	Yes	Supported by design
243SA		MPEG4 M-JPEG	1	704x576	2-way	4/4	-	-	Yes	Supported by design
247S		MPEG4 M-JPEG	1	704x576	1-way	1/1	-	-	Yes	Supported by design
2460		M-JEPG	4	-	-	4/4		-	Yes	Supported by design
M1011	5	H.264 MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	
M1011-W	5	H.264 MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	
M1031-W	5	H.264 MPEG4 M-JPEG	1	640x480	2-way	1/0	-	-	Yes	
M1054	5.15.1	H.264 M-JPEG	1	1024x600	2-way	1/1	Yes	-	Yes	
M1103	5.08	H.264 M-JPEG	1	640x480	-	-	Yes	-	Yes	
M1104		H.264 M-JPEG	1	1280x800	-	-	-	-	Yes	Supported by design
M1114	5.08	H.264 M-JPEG	1	1280x800	-	-	-	-	Yes	
M3011	5.01	H.264 MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	
M1113	5.08	H.264 M-JPEG	1	640x480	-	-	Yes	-	Yes	
M3014		H.264 M-JPEG	1	1280x800	-	-	-	-	Yes	Supported by design
M3203/M3203-V		H.264 M-JPEG	1	800x600	-	-	-	-	Yes	Supported by design
M3204/M3204-V		H.264 M-JPEG	1	1280x800	-	-	-	-	Yes	Supported by design
M7001	5.01	H.264 M-JPEG	1	720x480	-	-	Yes	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

AXIS										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
P1311	5.01	H.264 MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
P1343		H.264 M-JPEG	1		2-way	1/1	Yes	-	Yes	
P1344	5.06	H.264 M-JPEG	1	1280x800	2-way	1/1	Yes	-	Yes	
P1346	5.06	H.264 M-JPEG	1	2048x1536	2-way	1/1	-	-	Yes	
P3301	5.11	H.264 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
P3301-V		H.264 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	Supported by design
P3304		H.264 M-JPEG	1		2-way	1/1	-	-	Yes	Supported by design
P3343	5.06	H.264 M-JPEG	1	800x600	2-way	1/1	Yes	-	Yes	
P3343-V		H.264 M-JPEG	1	800x600	2-way	1/1	Yes	-	Yes	Supported by design
P3343-VE		H.264 M-JPEG	1	800x600	2-way	1/1	Yes	-	Yes	Supported by design
P3344	5.06	H.264 M-JPEG	1	1280x800	2-way	1/1	Yes	-	Yes	
P3344-V	5.06	H.264 M-JPEG	1	1280x800	2-way	1/1	Yes	-	Yes	
P3344-VE	5.07	H.264 M-JPEG	1	1280x800	2-way	1/1	Yes	-	Yes	
Note:	P3343 and P3344 series cameras support digital PTZ only.									
P5534	5.15.1	H.264 M-JPEG	1	1280x720	2-way	2/2	Yes	-	Yes	
Q1755	5.02	H.264 M-JPEG	1	1920x1080	2-way	1/1	Yes	-	Yes	
Note:	M-JPEG: Due to the HW constraints, the frame rate and audio will be impacted if resolution and quality are high.									
Q1910	5.11	H.264 M-JPEG	1	720x576	2-way	1/1	Yes	-	Yes	
Q1910-E		H.264 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

AXIS



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
Q6032-E	5.06.1	H.264 M-JPEG	1	704x576	-	-	Yes	-	Yes	
Q6034	5.15	H.264 M-JPEG	1	1280x800	-	2/2	Yes	-	Yes	
Q7401		H.264 M-JPEG	1	704x576	2-way	2/2	Yes	-	Yes	Supported by design
Q7404	5.02	H.264 M-JPEG	4	768x576	2-way	1/1	Yes	-	Yes	
Q7406		H.264 M-JPEG	6	704x576	-	-	Yes	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

BASLER



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
BIP-640C		H.264 MPEG4 M-JPEG	1	640x480	-	1/1	-	-	-	Supported by design
BIP-640C-DN		H.264 MPEG4 M-JPEG	1	640x480	-	1/1	-	-	-	Supported by design
BIP-1000C	BIP-1000c-1.3-0	H.264 MPEG4 M-JPEG	1	1024x768	-	1/1	-	-	-	
BIP-1000C-DN		H.264 MPEG4 M-JPEG	1	1024x768	-	1/1	-	-	-	Supported by design
BIP-1300C	BIP-1300c-1.3-0	H.264 MPEG4 M-JPEG	1	1280x960	-	1/1	-	-	-	
BIP-1300C-DN		H.264 MPEG4 M-JPEG	1	1280x960	-	1/1	-	-	-	Supported by design
BIP-1600C	BIP-1600c-1.3-0	H.264 MPEG4 M-JPEG	1	1600x1200	-	1/1	-	-	-	
BIP-1600C-DN		H.264 MPEG4 M-JPEG	1	1600x1200	-	1/1	-	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Bosch



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
NW-455	19500410	H.264 M-JPEG	1	704x576	-	-	-	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Brickcom



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
WCB-100A	v2.3.5.6.1	H.264 MPEG4 M-JPEG	1	1280x800	2-way	-	-	-	Yes	
WFB-100A	v2.3.7.8	H.264 MPEG4 M-JPEG	1	1280x800	2-way	1/0	-	-	Yes	
FD-100A	v2.3.7.8	H.264 MPEG4 M-JPEG	1	1280x800	2-way	1/0	-	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

CISCO



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
PVC-300	1.0.0	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	-	Yes	
WVC210	v1.1.0	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	Yes	
Note:	PTZ is only supported by external RS-485 device.									

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

CNB



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IBE3815NVR		H.264 MPEG4 M-JPEG	1	704x480	2-way	-	Yes	-	Yes	Supported by design
IBE3815PVR		H.264 MPEG4 M-JPEG	1	704x576	2-way	-	Yes	-	Yes	Supported by design
IBE5810NCR		H.264 MPEG4 M-JPEG	1	704x480	2-way	-	Yes	-	Yes	Supported by design
IBE5810PCR		H.264 MPEG4 M-JPEG	1	704x576	2-way	-	Yes	-	Yes	Supported by design
IDP4000VD		H.264 MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
IDP4000VR		H.264 MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
IDP4030VR	XNET.A1- 1.1.10.304	H.264 MPEG4 M-JPEG	1	1280x960	2-way	-	-	-	Yes	
IGP1000		H.264 MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	Yes	Supported by design
IGP1030		H.264 MPEG4 M-JPEG	1	1280x960	2-way	-	Yes	-	Yes	Supported by design
IJB2000		H.264 MPEG4 M-JPEG	1	704x576	2-way	-	Yes	-	Yes	Supported by design
INS2000	XNET.A1- 1.1.10.304	H.264 MPEG4 M-JPEG	1	704x480	2-way	-	Yes	-	Yes	
IPM3063N		H.264 MPEG4 M-JPEG	1	704x480	2-way	-	Yes	-	Yes	Supported by design
IPM3063P		H.264 MPEG4 M-JPEG	1	704x576	2-way	-	Yes	-	Yes	Supported by design
ISMC1063N	XNET.A1- 1.1.10.304	H.264 MPEG4 M-JPEG	1	704x480	2-way	-	Yes	-	Yes	
ISMC1063P		H.264 MPEG4 M-JPEG	1	704x576	2-way	-	Yes	-	Yes	Supported by design
ISS2765NW		H.264 MPEG4 M-JPEG	1	704x480	2-way	-	Yes	-	Yes	Supported by design
ISS2765PW		H.264 MPEG4 M-JPEG	1	704x576	2-way	-	Yes	-	Yes	Supported by design
IVP4000VR		H.264 MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
IVP4030VR		H.264 MPEG4 M-JPEG	1	1280x960	2-way	-	-	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

CNB



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IDC4000T	XNET.T1-1.0.10.0524	MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	
IVC4000T		MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Digimerge

DIGIMERGE

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DNS1010	2.74-wisHttp	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	-	-	
DND7100E	L.M. 1.6.16.03_de mo	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

D-Link



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DCS-2100		H.263	1	720x576	1-way	-	-	-	Yes	Supported by design
DCS-2100G		H.263	1	720x576	1-way	-	-	-	Yes	Supported by design
DCS-2120(TW)	0201tw	MPEG4	1	720x576	1-way	1/1	-	-	Yes	
DCS-2120		MPEG4	1	720x576	1-way	-	-	-	Yes	Supported by design
DCS-3110		MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	Supported by design
DCS-3220		MPEG4	1	720x576	2-way	1/1	-	-	Yes	Supported by design
DCS-3220G		MPEG4	1	720x576	2-way	1/1	-	-	Yes	Supported by design
DCS-3410		MPEG4 M-JPEG	1	704x576	1-way	1/1	-	-	Yes	Supported by design
DCS-3415	1	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
Note:	PTZ Support: zoom only.									
DCS-3420		MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	Supported by design
DCS-5220(TW)		MPEG4	1	720x576	1-way	-	Yes	-	Yes	Supported by design
DCS-5220	200	MPEG4	1	720x576	1-way	-	Yes	-	Yes	
DCS-5300	1.05	MPEG4	1	704x576	1-way	1/1	Yes	-	Yes	
DCS-5300G		H.263	1	720x576	1-way	1/1	Yes	-	Yes	Supported by design
DCS-5610		MPEG4 M-JPEG	1	720x576	2-way	1/1	Yes	-	Yes	Supported by design
DCS-6110	1	M-JPEG	1	720x576	-	1/1	-	-	Yes	
DCS-6111	1	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
DCS-6620	1.05	MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

D-Link



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DCS-6620G	1.05	MPEG4 M-JPEG	1	720x576	2-way	1/1	Yes	-	Yes	
DCS-900	1	MPEG4	1	640x480	1-way	-	-	-	Yes	
DCS-910	1	MPEG4	1	640x480	1-way	-	-	-	Yes	
DCS-920	1.03	M-JPEG	1	640x480	1-way	-	-	-	Yes	
DCS-950		MPEG4	1	640x480	1-way	-	-	-	Yes	Supported by design
DCS-950G		MPEG4	1	640x480	1-way	-	-	-	Yes	Supported by design
DCS-G900		M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
DVS-104		M-JPEG	4	720x576	-	4/2	-	-	Yes	Supported by design
DVS-301		H.263	1	704x576	1-way	1/1	-	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Dynacolor



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
nZH06X	CMOS-080118	MPEG4 M-JPEG	1	1280x960	2-way	1/1	-	-	-	
nZH10X	CMOS-080118	MPEG4 M-JPEG	1	1280x960	1-way	-	-	-	-	
nZH21X	CCD-cameraFw-IR-080108	MPEG4 M-JPEG	1	1280x960	2-way	1/1	-	-	-	
nNH221	CCD: CCD-cameraFw-100205P	MPEG4 M-JPEG H.264	1	1280x960	2-way	1/1	-	-	Yes	
nNH061	CCD: CCD-cameraFw-100205	MPEG4 M-JPEG H.264	1	1280x960	2-way	1/1	-	-	Yes	
V1 (indoor)	s/w: d20100317N S	M-JPEG H.264	1	1920x1080	1-way	-	-	-	Yes	
V1 (outdoor)	s/w: d20100317N S	M-JPEG H.264	1	1920x1080	-	-	-	-	Yes	
V6	s/w: d20100317N S	M-JPEG H.264	1	1920x1080	2-way	1/1	-	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Eneo



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
GLC-1401	1.36	MPEG4 M-JPEG	1	720x576	1-way	1/0	Yes	-	Yes	
GLC-1601	1.43	MPEG4 M-JPEG	1	720x576	1-way	1/0	Yes	-	Yes	
GLC-1602H	1.4	M-JPEG	1	720x576	1-way	1/0	Yes	-	Yes	
GLD-1401	1.4	MPEG4 M-JPEG	1	720x576	-	1/0	-	-	Yes	
GLD-1501	1.43	MPEG4 M-JPEG	1	720x576	1-way	1/0	-	-	Yes	
GLS-2101	1.45	MPEG4 M-JPEG	1	720x576	1-way	1/0	Yes	-	Yes	
Note:	PTZ is only supported by external RS-485 device.									

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

ETROVISION



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
EV3130AW		MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Supported by design
EV3130A		MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Supported by design
EV3131	2.4.8 Build 20081003	MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	-	
EV3830H/H P		MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	-	Supported by design
EV6130W		MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	-	Supported by design
EV6130/P		MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	-	Supported by design
EV6131HW		MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	-	Supported by design
EV6131H/H P		MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	-	Supported by design
EV6132A		MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Supported by design
EV6230A		MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Supported by design
EV6332		MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Supported by design
EV6333A		MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Supported by design
EV6530		MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Supported by design
EV6531A		MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Supported by design
EV6532A		MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

EverFocus



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
EVS100	1.1.0.5	MPEG4 M-JPEG	1	Full D1	1-way	0/1	Yes	-	-	
EVS400	1.1.5.0	MPEG4 M-JPEG	4	Full D1	2-way	4/0	Yes	-	-	
EVS750		MPEG4 M-JPEG	1	Full D1	1-way	1/1	-	-	-	Supported by design
EAN-850A	1.1.27	MPEG4 M-JPEG H.264	1	Full D1	-	1/1	-	-	Yes	
EZN-850	1.1.27	MPEG4 M-JPEG H.264	1	Full D1	-	1/1	z only	-	Yes	
EDN-800	1.1.27	MPEG4 M-JPEG H.264	1	Full D1	-	1/1	-	-	Yes	
EDN-850H	1.0.5	MPEG4 M-JPEG H.264	1	Full D1	-	1/1	-	-	Yes	
EAN900	1.1.34	MPEG4 M-JPEG H.264	1	1M	-	1/1	-	-	Yes	
EAN800AW		MPEG4 M-JPEG H.264	1	Full D1	-	1/1	-	-	Yes	Supported by design
EAN800A	1.1.34	MPEG4 M-JPEG H.264	1	Full D1	-	1/1	-	-	Yes	
EVS200A	1.0.5	MPEG4 M-JPEG H.264	2	CIF	-	2/2	Yes	-	Yes	
EVS200AW		MPEG4 M-JPEG H.264	2	CIF	-	2/2	Yes	-	Yes	Supported by design
EPN2700		MPEG4 M-JPEG H.264	1	Full D1	-	4/2	Yes	-	Yes	Supported by design
EPN3100	1.0.4	MPEG4 M-JPEG H.264	1	Full D1	-	4/2	Yes	-	Yes	
EPN3600		MPEG4 M-JPEG H.264	1	Full D1	-	4/2	Yes	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

EYEVIEW



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IPS-900NIC	2.4.9	MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

FINE



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
TCP-690		MPEG4 M-JPEG	1	720x576	1-way	2/2	-	-	-	Supported by design
TCP-690DN		MPEG4 M-JPEG	1	720x576	1-way	2/2	-	-	-	Supported by design
TCP-HP930		MPEG4 M-JPEG	1	720x576	1-way	2/2	-	-	-	Supported by design
WB-8211SD		MPEG4 M-JPEG	1	720x576	1-way	2/4	-	-	-	Supported by design
WB-8411		MPEG4 M-JPEG	4	720x576	1-way	4/1	-	-	-	Supported by design
CDV-3V930		MPEG4 M-JPEG	1	720x576	1-way	1/1	-	-	-	Supported by design
TCP-690U		MPEG4 M-JPEG	1	720x576	1-way	2/2	-	-	-	Supported by design
TCP-HP930U		MPEG4 M-JPEG	1	720x576	1-way	2/2	-	-	-	Supported by design
WB-8211SDU		MPEG4 M-JPEG	1	720x576	1-way	2/4	-	-	-	Supported by design
CDV-3V930U		MPEG4 M-JPEG	1	720x576	1-way	1/1	-	-	-	Supported by design
EP-936		MPEG4 M-JPEG	1	720x576	1-way	-	Yes	-	-	Supported by design
EP-908		MPEG4 M-JPEG	1	720x576	1-way	-	Yes	-	-	Supported by design
EP-601		MPEG4 M-JPEG	1	720x576	1-way	-	Yes	-	-	Supported by design
EP-201		MPEG4 M-JPEG	1	720x576	1-way	-	Yes	-	-	Supported by design
EP-221		MPEG4 M-JPEG	1	720x576	1-way	-	Yes	-	-	Supported by design
EP-221DN		MPEG4 M-JPEG	1	720x576	1-way	-	Yes	-	-	Supported by design
MD-D1200	V3.2.56_F	MPEG4 M-JPEG	1	720x576	1-way	-	Yes	-	Yes	
Note:	Not integrate I/O									
TCP670DNU	V3.2.50_F	MPEG4 M-JPEG	1	720x576	1-way	-	-	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

FINE



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
Note:	Not integrate I/O									
TCP680DNU	V3.2.50_F	MPEG4 M-JPEG	1	720x576	1-way	-	-	-	Yes	
Note:	Not integrate I/O									

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

HIKVISION										
<i>HIKVISION</i>										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DS-2DF1	V2.2 Build 20090625	H.264	1	1600x1200	2-way	2/2	Yes	-	-	
DS-2CD852MF-E		MPEG4	1	1600x1200	2-way	1/1	Yes	-	-	Supported by design
DS-2CD802PF	V2.0 build 090522	H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	
DS-2CD802NF		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Tested by manufacturer
DS-2CD812PF		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Tested by manufacturer
DS-2CD812NF		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Tested by manufacturer
DS-2CD832PF		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Tested by manufacturer
DS-2CD832NF		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Tested by manufacturer
DS-2CD892PF		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Tested by manufacturer
DS-2CD892NF		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Tested by manufacturer
DS-2CD802PF-E		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD802NF-E		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD812PF-E		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD812NF-E		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD832PF-E		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD832NF-E		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD892PF-E		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD892NF-E		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD812PF-IR1		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

HIKVISION



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DS-2CD812NF-IR1		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD832PF-IR1		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD832NF-IR1		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD892PF-IR1		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD892NF-IR1		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD812PF-IR3		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD812NF-IR3		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD832PF-IR3		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD832NF-IR3		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD892PF-IR3		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD892NF-IR3		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD702PF		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD702NF		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD712PF	V2.0 build 090522	H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	
DS-2CD712NF		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD732PF		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD732NF		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD792PF		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD792NF		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

HIKVISION										
<i>HIKVISION</i>										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DS-2CD702P-FB		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD702N-FB		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD712P-FB		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD712N-FB		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD732PF-FB		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Supported by design
DS-2CD732NF-FB		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Supported by design
DS-2CD792PF-FB		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Supported by design
DS-2CD792NF-FB		H.264 MPEG4	1	704x576	2-way	1/1	-	-	-	Supported by design
DS-6101HFI-IP	V2.0 Build 20090522	H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	
DS-2CD852MF-E	V2.0 build 20090430	MPEG4	1	1600x1200	2-way	1/1	Yes	-	-	
DS-2CD752MF-E		MPEG4	1	1600x1200	2-way	1/1	Yes	-	-	Tested by manufacturer
DS-2CD752MF-FB		MPEG4	1	1600x1200	2-way	1/1	Yes	-	-	Tested by manufacturer
DS-2CD752MF-FH		MPEG4	1	1600x1200	2-way	1/1	Yes	-	-	Supported by design
DS-2CD862MF-E		MPEG4	1	1280x720	2-way	1/1	Yes	-	-	Tested by manufacturer
DS-2CD762MF		MPEG4	1	1280x960	2-way	1/1	-	-	-	Tested by manufacturer
DS-2CD762MF-E		MPEG4	1	1280x960	2-way	1/1	-	-	-	Supported by design
DS-2CD762MF-FH		MPEG4	1	1280x960	2-way	1/1	-	-	-	Supported by design
DS-2CD762MF-FB(Hs)		MPEG4	1	1280x960	2-way	1/1	-	-	-	Supported by design
DS-2CD812P(N)-IR5		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

HIKVision



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DS-2CD832P(N)-IR5		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD892P(N)-IR5		H.264 MPEG4	1	704x576	2-way	1/1	Yes	-	-	Supported by design
DS-2CD852F		MPEG4	1	1600x1200	2-way	1/1	Yes	-	-	Supported by design
DS-2CD752F-E		MPEG4	1	1600x1200	2-way	1/1	Yes	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

HiTRON




Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
HNCB-E1SN		MPEG4	1	720x480	-	-	-	-	-	Supported by design
HNG-E1SAW0S4	4.1.2-50	MPEG4	1	720x480	1-way	-	-	-	-	
HWD125MN	4.1.2-50	MPEG4	1	720x480	1-way	-	Yes	-	-	
HECMC4VOC4		MPEG4	1	640x480	1-way	-	-	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

iCANTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
I CanView220		MPEG4	1	720x576	2-way	1/1	-	-	-	Supported by design
I CanView222		MPEG4	1	720x576	2-way	1/1	-	-	-	Supported by design
I CanView230		MPEG4	1	720x576	2-way	1/1	-	-	-	Supported by design
I CanView232		MPEG4	1	720x576	2-way	1/1	-	-	-	Supported by design
I CanView240		MPEG4	1	720x576	2-way	4/2	Yes	-	-	Supported by design
I CanView250	2.2.2	MPEG4	1	720x576	2-way	4/2	Yes	-	-	
I CanView260		MPEG4	1	720x576	2-way	1/1	-	-	-	Supported by design
I CanView270		MPEG4	1	720x576	2-way	2/1	Yes	-	-	Supported by design
I CanView280		MPEG4	1	720x576	2-way	1/1	-	-	-	Supported by design
I CanView290		MPEG4	1	720x576	2-way	1/1	Yes	-	-	Supported by design
I Canserver 510		MPEG4	1	720x576	2-way	1/1	-	-	-	Supported by design
iCanView362MP	v1.0.15	M-JPEG H264	1	720x480	2-way	1/1	-	-	-	
iCanView332MP	v1.0.19	M-JPEG H264	1	1600x1200	2-way	1/1	Yes	-	-	
iCanView350MP	v1.0.19	M-JPEG H264	1	720x480	2-way	4/2	Yes	-	-	
iCanServer612	v1.0.19	M-JPEG H264	1	720x480	2-way	1/1	Yes	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

IQinVision



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IQ040S	V3.1/6	M-JPEG	1	720x480	-	-	-	-	-	Supported by design
IQ041S	V3.1/6	M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
IQ042S	V3.1/6	M-JPEG	1	1600x1200	-	-	-	-	-	
IQD40S	V3.1/6	M-JPEG	1	720x480	-	-	-	-	-	Supported by design
IQD41S	V3.1/6	M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
IQD42S	V3.1/6	M-JPEG	1	1600x1200	-	-	-	-	-	
IQ540S	V3.1/6	M-JPEG	1	720x480	-	-	-	-	-	Supported by design
IQ541S	V3.1/6	M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
IQ542S	V3.1/6	M-JPEG	1	1600x1200	-	-	-	-	-	
IQD30S	V3.1/6	H.264 M-JPEG	1	720x480	1-WAY	-	-	-	-	Supported by design
IQD31S	V3.1/6	H.264 M-JPEG	1	1280x720	1-WAY	-	-	-	-	
IQA25S	V2.9/6	H.264 M-JPEG	1	1280x1024	1-WAY	1/1	-	-	-	
Note:	M-JPEG: not support audio function									
IQeye301		M-JPEG	1		-	1/1	-	-	-	Supported by design
IQeye301m		M-JPEG	1		-	1/1	-	-	-	Supported by design
IQeye301w		M-JPEG	1		-	1/1	-	-	-	Supported by design
IQeye302		M-JPEG	1		-	1/1	-	-	-	Supported by design
IQeye302w		M-JPEG	1		-	1/1	-	-	-	Supported by design
IQeye303		M-JPEG	1		-	1/1	-	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

IQinVision



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IQeye303w		M-JPEG	1		-	1/1	-	-	-	Supported by design
IQeye501		M-JPEG	1	1280x1024	-	1/1	-	-	-	Supported by design
IQeye510	B2.8/608	M-JPEG	1	752x480	-	-	-	-	-	
IQeye511	V2.8/6	M-JPEG	1		-	-	-	-	-	
IQeye601		M-JPEG	1		-	1/1	-	-	-	Supported by design
IQeye602		M-JPEG	1		-	1/1	-	-	-	Supported by design
IQeye603		M-JPEG	1		-	1/1	-	-	-	Supported by design
IQeye701	V2.8/6	M-JPEG	1	1280x1024	-	1/1	-	-	-	
IQeye702	V2.8/6	M-JPEG	1	1600x1200	-	1/1	-	-	-	
IQeye703	V2.8/6	M-JPEG	1	2048x1536	-	1/1	-	-	-	
IQeye705	V2.8/6	M-JPEG	1	2560x1920	-	1/1	-	-	-	
IQeye751		M-JPEG	1	1280x1024	-	1/1	-	-	-	Supported by design
IQeye752	V2.8/6	M-JPEG	1	1600x1200	-	1/1	-	-	-	
IQeye753		M-JPEG	1	2048x1536	-	1/1	-	-	-	Supported by design
IQeye755	V2.8/6	M-JPEG	1	2560x1920	-	1/1	-	-	-	
IQeye855	V2.8/6	M-JPEG	1	2560x1920	-	1/1	-	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

JVC



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
VN-C20U		M-JPEG	1	640x480	-	2/2	-	-	-	Supported by design
VN-E4(U)		M-JPEG	4	640x480	Yes	4/1	-	-	-	Supported by design
VN-C205U		M-JPEG	1	640x480	-	0/0	Yes	-	-	Supported by design
VN-C215U		M-JPEG	1	640x480	-	2/2	-	-	-	Supported by design
VN-C655U		M-JPEG	1	640x480	-	0/0	Yes	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

LevelOne										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
FCS-0010		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
FCS-0020	1.0.07	MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	
FCS-1010	0102d	H.263	1	720x576	1-way	1/1	Yes	-	Yes	
FCS-1030V1.0		H.263	1	720x576	1-way	-	-	-	Yes	Supported by design
FCS-1030V2.0		MPEG4	1	720x576	1-way	-	-	-	Yes	Supported by design
FCS-1040	0102a	MPEG4 M-JPEG	1	720x576	2-way	1/1	Yes	-	Yes	
FCS-1050		H.263	1	720x576	1-way	1/1	-	-	Yes	Supported by design
FCS-1060	0202a	MPEG4	1	720x576	1-way	-	Yes	-	Yes	
FCS-1070		MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	Supported by design
FCS-1081		MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
FCS-1081A		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	Supported by design
FCS-1091		MPEG4 M-JPEG	1	640x480	2-way	2/2	-	-	Yes	Supported by design
FCS-1101		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
FCS-3000	0101a	MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	
FCS-3021		MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	Supported by design
FCS-4010		MPEG4 M-JPEG	1	720x576	1-way	4/1	Yes	-	Yes	Supported by design
FCS-4x00		MPEG4 M-JPEG	1	704x480	2-way	4/1	Yes	-	Yes	Supported by design
FCS-5011	0100c	MPEG4 M-JPEG	1	720x480	2-way	1/1	-	-	Yes	
FCS-5030	0102g	MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List


V 1.4.0 (2010.08.09)

LevelOne										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
Note:	No audio support in M-JPEG format.									
FCS-7011		MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	-	Yes	Supported by design
WCS-0010		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
WCS-0020		MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	Yes	Supported by design
WCS-1090		MPEG4 M-JPEG	1	640x480	2-way	2/2	-	-	Yes	Supported by design
WCS-2010V1.0		H.263	1	720x576	1-way	1/1	Yes	-	Yes	Supported by design
WCS-2010V2.0		H.263	1	720x576	1-way	1/1	Yes	-	Yes	Supported by design
WCS-2030V1.0	0200d	H.263	1	720x576	1-way	-	-	-	Yes	
WCS-2030V2.0		H.263	1	720x576	1-way	-	-	-	Yes	Supported by design
WCS-2030V3.0		MPEG4	1	720x576	1-way	-	-	-	Yes	Supported by design
WCS-2040	0101b	MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	
WCS-2060		MPEG4	1	720x576	1-way	-	-	-	Yes	Supported by design
WCS-2070	0100b	MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	
FCS-3031	V1.0.01	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
FCS-3051	V1.0.01	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
FCS-1131	s/w: L20100315N S	M-JPEG H.264	1	1920x1080	2-way	1/1	-	-	Yes	
FCS-1141	CCD: CCD-cameraFw-100205	M-JPEG MPEG4 H.264	1	1280x960	2-way	1/1	-	-	Yes	
Note:	Detail FW version : CCD: CCD-cameraFw-100205 ; s/w: L20100312NS									
FCS-3071	s/w: L20100315N S	M-JPEG H.264	1	1920x1080	1-way	0/0	-	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

LevelOne										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
FCS-0030		M-JPEG MPEG4 H.264	1	1280x800	2-way	0/0	-	-	Yes	Supported by design
WCS-0030	v1.0.0.7	M-JPEG MPEG4 H.264	1	1280x800	2-way	0/0	-	-	Yes	
FCS-1121	v1.0.0.10	M-JPEG MPEG4 H.264	1	1280x800	2-way	1/0	-	-	Yes	
FCS-3061	v1.0.0.17	M-JPEG MPEG4 H.264	1	1280x800	2-way	1/0	-	-	Yes	
FCS-4020	0100a	MPEG4 M-JPEG	1	704x576	2-way	4/1	Yes	-	Yes	
FCS-1040 v3.0	0100a	MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	
WCS-2040 v3.0	0100b	MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	
FCS-7111	0100c	MPEG4 M-JPEG H.264	1	1600x1200	2-way	1/1	-	-	Yes	
FCS-1151	0100a	M-JPEG MPEG4 H.264	1	1600x1200	2-way	1/1	-	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Linksys



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
PVC2300	V1.0.1	MPEG4 M-JPEG	1	640x480	2-way	2/2	Yes	-	Yes	
WVC210	V1.1.0	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	Yes	
WVC2300	V1.0.1	MPEG4 M-JPEG	1	640x480	2-way	2/2	Yes	-	Yes	
Note:	PTZ is only supported by external RS-485 device.									

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)


LOREX



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
LNE3003	LM1.6.16.03	MPEG4 M-JPEG	1	640x480	Two-way	0/0	-	-	Yes	

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Lumenera										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
le045c		M-JPEG	1	720x480	-	-	-	-	-	Supported by design
le045c-dn		M-JPEG	1	720x480	-	-	-	-	-	Supported by design
le075c		M-JPEG	1	640x480	-	-	-	-	-	Supported by design
le075c-dn		M-JPEG	1	640x480	-	-	-	-	-	Supported by design
le11059c		M-JPEG	1	4000x2656	-	-	-	-	-	Supported by design
le165c		M-JPEG	1	1376x1032	-	-	-	-	-	Supported by design
le165c-dn		M-JPEG	1	1376x1032	-	-	-	-	-	Supported by design
le175c		M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
le175c-dn		M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
le259c		M-JPEG	1	1920x1080	-	-	-	-	-	Supported by design
le275c		M-JPEG	1	1600x1200	-	-	-	-	-	Supported by design
le275c-dn		M-JPEG	1	1600x1200	-	-	-	-	-	Supported by design
le375c		M-JPEG	1	2048x1536	-	-	-	-	-	Supported by design
le375c-dn		M-JPEG	1	2048x1536	-	-	-	-	-	Supported by design
li165c	5626	M-JPEG	1	1376x1032	-	-	-	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
D12D-IT		MxPEG M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
D12D-Sec		MxPEG M-JPEG	1	2048x1536	1-way	-	-	-	-	Supported by design
D22M-Basic		MxPEG M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
D22M-IT	MX-V3.4.0.9	MxPEG M-JPEG	1	640x480	1-way	-	-	-	-	
D22M-Sec		MxPEG M-JPEG	1	2048x1536	1-way	-	-	-	-	Supported by design
M10D	M10-V2.2.2.17	MJPEG	1	2048x1536	1-way	-	-	-	-	
M12D-IT		MxPEG M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
M12D-Sec	MX-V3.4.0.9	MxPEG M-JPEG	1	2048x1536	1-way	-	-	-	-	
M12D-Web		MxPEG M-JPEG	1	2048x1536	1-way	-	-	-	-	Supported by design
M22M-IT		MxPEG M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
M22M-Sec		MxPEG M-JPEG	1	2048x1536	1-way	-	-	-	-	Supported by design
Q22M-Basic		MxPEG M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
Q22M-Sec	MX-V3.4.5.10	MxPEG M-JPEG	1	2048x1536	1-way	-	-	-	-	
Q24-Basic		MxPEG M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
Q24-Sec	MX-V4.0.1.7	MxPEG M-JPEG	1	2048x1536	1-way	-	-	-	-	
D24M-Basic		MxPEG M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
D24M-IT		MxPEG M-JPEG	1	640x480	1-way	2/2	-	-	-	Supported by design
D24M-Sec	MX-V4.0.1.15	MxPEG M-JPEG	1	2048x1536	1-way	2/2	-	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Moxa




Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
Vport 25	1.0	MPEG4 M-JPEG	1	720x480	2-way	1/1	Yes	-	Yes	
Vport 251	1.0	MPEG4 M-JPEG	1	720x480	2-way	1/1	Yes	-	Yes	
Vport 254	1.0	MPEG4 M-JPEG	4	720x480	2-way	4/2	Yes	-	Yes	
Vport 351	2.3	MPEG4 M-JPEG	1	720x480	2-way	2/2	Yes	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Panasonic										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
BB-HCE481		M-JPEG	1	640x480	2-way	2/1	-	-	Yes	Supported by design
BB-HCM100		M-JPEG	1	640x480	1-way	2/1	Yes	-	Yes	Supported by design
BB-HCM110		M-JPEG	1	640x480	1-way	2/1	Yes	-	Yes	Supported by design
BB-HCM311		M-JPEG	1	640x480	2-way	2/1	Yes	-	Yes	Supported by design
BB-HCM331	1.3	M-JPEG	1	640x480	2-way	2/1	Yes	-	Yes	
BB-HCM371		M-JPEG	1	640x480	1-way	2/1	-	-	Yes	Supported by design
BB-HCM381	1.32	M-JPEG	1	640x480	2-way	1/1	Yes	-	Yes	
BB-HCM403		M-JPEG	1	640x480	2-way	2/1	-	-	Yes	Supported by design
BB-HCM511	3.20R01	MPEG4 M-JPEG	1	640x480	2-way	2/1	Yes	-	Yes	
BB-HCM515	3.14R01	MPEG4 M-JPEG	1	1280x1024	2-way	2/1	-	-	Yes	
Note:	No audio support in M-JPEG format @ 1280x1024.									
BB-HCM527	3.51R00	MPEG4 M-JPEG	1	640x480	2-way	2/1	-	-	Yes	
BB-HCM531	3.51R00	MPEG4 M-JPEG	1	640x480	2-way	2/1	-	-	Yes	
BB-HCM547	3.60R00	MPEG4 M-JPEG	1	640x480	2-way	2/1	Yes	-	Yes	
BB-HCM580		MPEG4 M-JPEG	1	640x480	2-way	2/1	-	-	Yes	Supported by design
BB-HCM581	3.21R00	MPEG4 M-JPEG	1	640x480	2-way	2/1	Yes	-	Yes	
BB-HCS301		M-JPEG	1	640x480	1-way	1/1	-	-	Yes	Supported by design
BL-C1		M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
BL-C10		M-JPEG	1	640x480	-	-	Yes	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Panasonic										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
BL-C111	3.10R01	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	-	Yes	
BL-C131		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	Supported by design
BL-C20		M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
BL-C30		M-JPEG	1	640x480	-	-	Yes	-	Yes	Supported by design
BL-C101A	3.52R00	MPEG4 M-JPEG	1	640x480	1-way	1/0	-	-	Yes	
BL-C121A	3.52R00	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	-	Yes	
BL-C140A	3.51R00	MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	
BL-C160	3.51R01	MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	
BB-HCM701	4.30R00	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/0	-	-	Yes	
BB-HCM705A	4.30R00	H.264 MPEG4 M-JPEG	1	1280x960	1-way	1/0	Yes	-	Yes	
BB-HCM715A	4.30R00	H.264 MPEG4 M-JPEG	1	1280x960	2-way	2/1	Yes	-	Yes	
BB-HCM735A	4.30R00	H.264 MPEG4 M-JPEG	1	1280x960	2-way	2/1	Yes	-	Yes	
KX-HCM110		M-JPEG	1	640x480	1-way	2/1	-	-	Yes	Supported by design
KX-HCM280A		M-JPEG	1	640x480	-	1/1	-	-	Yes	Supported by design
DG-NF284		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
DG-NF302	1.5	MPEG4 M-JPEG	1	1280x960	1-way	-	-	-	-	
DG-NP240		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
DG-NP244	1.70J2	MPEG4 M-JPEG	1	640x480	1-way	-	-	-	-	
DG-NP304	1.5	MPEG4 M-JPEG	1	1280x960	2-way	-	-	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Panasonic										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DG-NS202		MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	Supported by design
DG-NS202A	2.60J3	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	
DG-NS950	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	
DG-NS954	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	
DG-NW960	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	
DG-NW964	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	
WJ-NT304	1.04	M-JPEG	4	640x480	-	-	Yes	-	-	
WJ-NT314		M-JPEG	4	640x480	1-way	-	Yes	-	-	Supported by design
WV-NF284	v1.02	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	-	-	
WV-NF302	1.40E4_1.06	MPEG4 M-JPEG	1	1280x960	2-way	-	-	-	-	
WV-NM100		MPEG4 M-JPEG	1	640x480	-	-	Yes	-	-	Supported by design
WV-NP1000		M-JPEG	1	1280x960	1-way	-	-	-	-	Supported by design
WV-NP1004	1.21	M-JPEG	1	1280x960	1-way	-	-	-	-	
WV-NP240		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
WV-NP244		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
WV-NP304	1.50E5_1.06	MPEG4 M-JPEG	1	1280x960	2-way	-	-	-	-	
WV-NP472		M-JPEG	1	640x480	-	-	-	-	-	Supported by design
WV-NP502	1.00	H.264 MPEG4 M-JPEG	1	2048x1536	2-way	-	-	-	-	
WV-NS202		MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Panasonic



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
WV-NS202A	2.6	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	
WV-NS324	2.01	M-JPEG	1	640x480	-	-	Yes	-	-	
WV-NS950	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	
WV-NS954	1.06E0	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	
Note:	Audio is abnormal in MPEG4 format.									
WV-NW484	1.10ED	MPEG4 M-JPEG	1	640x480	-	-	-	-	-	
WV-NW502S	1.00	H.264 MPEG4 M-JPEG	1	2048x1536	2-way	-	-	-	-	
WV-NW960	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	
WV-NW964	1.40E3	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Pixord



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
100		M-JPEG	1	704x480	-	-	-	-	-	Supported by design
120/126/128		M-JPEG	2	704x480	-	4/1	-	-	-	Supported by design
200/206		M-JPEG	1	704x480	-	4/1	-	-	-	Supported by design
201		M-JPEG	1	704x480	-	4/1	-	-	-	Supported by design
205		M-JPEG	1	704x480	-	4/1	-	-	-	Supported by design
207		M-JPEG	1	704x480	-	4/1	-	-	-	Supported by design
240		M-JPEG	4	704x480	-	4/1	-	-	-	Supported by design
241		M-JPEG	4	704x480	-	4/1	-	-	-	Supported by design
261		M-JPEG	1	704x480	-	1/0	Yes	-	-	Supported by design
262		M-JPEG	1	704x480	-	4/1	Yes	-	-	Supported by design
263		M-JPEG	1	704x480	-	4/1	Yes	-	-	Supported by design
300		M-JPEG	1	640x480	1-way	-	-	-	-	Supported by design
400/42X	v2.46R03.01.PX	MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	
461		MPEG4 M-JPEG	1	704x480	1-way	4/1	Yes	-	-	Supported by design
463		MPEG4 M-JPEG	1	704x480	1-way	1/0	Yes	-	-	Supported by design
1000		M-JPEG	1	704x480	-	4/1	Yes	-	-	Supported by design
1401		MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Supported by design
2000		M-JPEG	2	704x480	-	4/1	Yes	-	-	Supported by design
4000		M-JPEG	4	704x480	-	4/1	Yes	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Pixord



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
405		MPEG4	1	640x480	2-way	-	-	-	-	Supported by design
410		MPEG4 M-JPEG	1	704x480	2-way	1/1	Yes	-	-	Supported by design
405M		MPEG4 M-JPEG	1	1280x1024	2-way	-	-	-	-	Supported by design
411/412		MPEG4 M-JPEG	1	704x480	2-way	1/1	-	-	-	Supported by design
415M	V3.2.48.R02. PN	MPEG4 M-JPEG	1	1280x1024	1-way	-	-	-	-	
416	V3.2.48.R02. PN	MPEG4 M-JPEG	1	704x480	2-way	1/1	Yes	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

PLANET



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
ICA-510		MPEG4	1	640x480	2-way	-	-	-	Yes	Supported by design
ICA-700		MPEG4	1	640x480	2-way	-	-	-	Yes	Supported by design
ICA-151W		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
ICA-151		MPEG4 M-JPEG	1	640x480	2-way	-	-	-	Yes	Supported by design
ICA-750	1005	MPEG4 M-JPEG	1	640x480	2-way	2/2	-	-	Yes	
ICA-107W		M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
ICA-107P		M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
ICA-107		M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
ICA-108		MPEG4	1	640x480	2-way	-	-	-	Yes	Supported by design
ICA-108W		MPEG4	1	640x480	2-way	-	-	-	Yes	Supported by design
ICA-120	3.0.2.2134	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
ICA-230		MPEG4	1	640x480	2-way	-	Yes	-	Yes	Supported by design
ICA-230W		MPEG4	1	640x480	2-way	-	Yes	-	Yes	Supported by design
ICA-230P		MPEG4	1	640x480	2-way	-	Yes	-	Yes	Supported by design
ICA-M230		MPEG4	1	1280x1024	2-way	-	Yes	-	Yes	Supported by design
ICA-310		MPEG4	1	640x480	-	-	Yes	-	Yes	Supported by design
ICA-310W		MPEG4	1	640x480	-	-	Yes	-	Yes	Supported by design
ICA-312		MPEG4	1	640x480	-	-	Yes	-	Yes	Supported by design
ICA-312v2	3.0.2.2134	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

PLANET




Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
ICA-350		MPEG4	1	640x480	-	-	Yes	-	Yes	Supported by design
ICA-350-V2	3.0.2.2134	MPEG4 M-JPEG	1	640x480	2-way	1/1	Yes	-	Yes	
ICA-501		MPEG4	1	640x480	2-way	-	Yes	-	Yes	Supported by design
ICA-525		MPEG4	1	640x480	2-way	1/1	Yes	-	Yes	Supported by design
ICA-530		MPEG4	1	640x480	2-way	-	Yes	-	Yes	Supported by design
ICA-651		MPEG4	1	640x480	2-way	1/1	Yes	-	Yes	Supported by design
ICA-601		MPEG4	1	640x480	2-way	1/1	Yes	-	Yes	Supported by design
IVS-110		MPEG4	1	640x480	2-way	1/1	Yes	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List


V 1.4.0 (2010.08.09)

Samsung										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SCC-C6475	2	MPEG4 M-JPEG	1	704x480	-	-	Yes	-	-	
SNC-B2315	2.11	MPEG4 M-JPEG	1	720x576	2-way	2/2	-	Yes	-	
SNC-B5395	2.10	MPEG4 M-JPEG	1	720x576	2-way	2/2	-	Yes	-	
SNC-B2331	1.00	H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	Yes	-	
SNC-B2335	1.01	H.264 MPEG4 M-JPEG	1	720x576	2-way	2/2	-	Yes	-	
SNC-B5368	1.00	H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	Yes	-	
SNC-B5399	1.01	H.264 MPEG4 M-JPEG	1	720x576	2-way	2/2	-	Yes	-	
SNC-C6225	1.01	MPEG4 M-JPEG	1	720x576	2-way	2/1	Yes	Yes	-	
SNC-C7225	1.01	MPEG4 M-JPEG	1	720x576	2-way	2/1	Yes	Yes	-	
SNC-C7478	v1.01_09062 5	MPEG4 M-JPEG	1	720x576	2-way	8/4	Yes	Yes	-	
SNC-M300	v2.11_09072 9	MPEG4 M-JPEG	1	2048x1536	2-way	2/2	-	Yes	-	
SNP-3300A	2.8.4	MPEG4 M-JPEG	1	D1	-	-	-	-	-	
SNB-2000		H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	-	-	Supported by design
SNB-3000		H.264 MPEG4 M-JPEG	1	720x576	2-way	2/2	-	-	-	Supported by design
SND-3080		H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	-	-	Supported by design
SNV-3080		H.264 MPEG4 M-JPEG	1	720x576	2-way	2/2	-	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Santec										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SNC-390DN/W	1.5	MPEG4 M-JPEG	1	720x576	2-way	1/1	Yes	-	Yes	
SNC-5211R/W	1.5	MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	
SNC-5651R/W	1.5	MPEG4 M-JPEG	1	720x576	2-way	1/1	Yes	-	Yes	
Note:	PTZ only support zoom in/out									
SNC - 620/W		MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	Supported by design
SNC-670ID/W	1.3	MPEG4 M-JPEG	1	720x576	2-way	1/1	Yes	-	Yes	
SNC-5211MIR	3.1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	
SNC-6201M	3.1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	
SNC-3901MDN	3.5	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	Yes	-	Yes	Test by manufacturer
SNC-P3601M	3.5	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	Test by manufacturer

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List


V 1.4.0 (2010.08.09)

Sanyo										
SANYO										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
VCC-HDN1		H.264 M-JPEG	1	2288x1712	-	2/1	Yes	-	-	Supported by design
VCC-HD2500	CAM MAIN 1.00-10	H.264 M-JPEG	1	2288x1712	2-way	2/2	-	-	-	
Note:	Detail FW version: CAM MAIN 1.00-10 ; CAM SUB 1.00-00 ; NET MAIN 1.00-06 ; NET SUB 1.00-01									
VCC-HD2500P	CAM MAIN 1.00-10	H.264 M-JPEG	1	2288x1712	2-way	2/2	-	-	-	
Note:	Detail FW version: CAM MAIN 1.00-10 ; CAM SUB 1.00-00 ; NET MAIN 1.00-06 ; NET SUB 1.00-01									
VCC-HD3500		H.264 M-JPEG	1	2288x1712	2-way	2/2	-	-	-	Supported by design
VDC-HD3500		H.264 M-JPEG	1	2288x1712	2-way	2/2	-	-	-	Supported by design
VDC-HD3500p		H.264 M-JPEG	1	2288x1712	2-way	2/2	-	-	-	Supported by design
VCC-HD2100		H.264 M-JPEG	1	2288x1712	-	2/2	-	-	-	Supported by design
VCC-HD2100P		H.264 M-JPEG	1	2288x1712	-	2/2	-	-	-	Supported by design
VCC-HD2300		H.264 M-JPEG	1	2288x1712	-	2/2	-	-	-	Supported by design
VCC-HD2300P		H.264 M-JPEG	1	2288x1712	-	2/2	-	-	-	Supported by design
VDC-HD3100		H.264 M-JPEG	1	2288x1712	-	2/2	-	-	-	Supported by design
VDC-HD3100P		H.264 M-JPEG	1	2288x1712	-	2/2	-	-	-	Supported by design
VCC-HD3300		H.264 M-JPEG	1	2288x1712	-	2/2	-	-	-	Supported by design
VDC-HD3300	MAIN 1.00-14	H.264 M-JPEG	1	2288x1712	-	2/2	-	-	-	
Note:	Detail FW version: MAIN 1.00-14 ; SUB 1.00-02									
VDC-HD3300P		H.264 M-JPEG	1	2288x1712	-	2/2	-	-	-	Supported by design
VCC-HD4600	CAM MAIN 1.00-05	H.264 M-JPEG	1	2288x1712	2-way	2/2	Yes	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Sanyo										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
Note:	Detail FW version: CAM MAIN 1.00-05 ; CAM SUB 1.00-01; NET MAIN 1.00-04 ; NET SUB 1.00-04 PTZ only support zoom in/out									
VCC-HD4600P		H.264 M-JPEG	1	2288x1712	2-way	2/2	Yes	-	-	Supported by design
Note:	PTZ only support zoom in/out									
VCC-HD5400		H.264 M-JPEG	1	2288x1712	2-way	4/2	Yes	-	-	Supported by design
VCC-HD5400P		H.264 M-JPEG	1	2288x1712	2-way	4/2	Yes	-	-	Supported by design
VCC-HD5600	CAM MAIN 1.00-04	H.264 M-JPEG	1	2288x1712	2-way	8/2	Yes	-	-	
Note:	Detail FW version: CAM MAIN 1.00-04 ; CAM SUB 1.00-00 ; MEC MAIN 1.04-00 ; I/O MAIN 1.03-00 ; NET MAIN 1.00-04 ; NET SUB 1.00-02									
VCC-HD5600P		H.264 M-JPEG	1	2288x1712	2-way	8/2	Yes	-	-	Supported by design
VDC-DP9585P	2.00-00 <M08101001 >	M-JPEG	1	640x480	2-way	-	Yes	-	-	
VDC-DP9584N	2.00-00 <M08101001 >	M-JPEG	1	640x480	2-way	-	Yes	-	-	
VCC-9800P	2.00-00 <H08070300 >	H.264 M-JPEG	1	720x576	2-way	-	Yes	-	-	
VCC-9800NA	2.00-00 <H08070300 >	H.264 M-JPEG	1	720x480	2-way	-	Yes	-	-	
VCC-ZM600N		H.264 M-JPEG	1	720x576	-	-	Yes	-	-	Supported by design
Note:	PTZ only support zoom in/out									

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Seorim




Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SVC-3030/41NR-DN	SVC-3030 version #5113	MPEG4 M-JPEG	1	704x480	1-way	1/1	-	-	-	
SVG-3110	SVG3110 version #5057	MPEG4	1	352x240	1-way	1/1	Yes	-	-	
SVG-3410	SVG-3410 #304	MPEG4	4	352x240	1-way	4/4	Yes	-	-	
SVD-3020-PTZ	SVD-3020 version #5110	MPEG4 M-JPEG	1	704x576	1-way	4/1	Yes	-	-	
SVC-302x		MPEG4 M-JPEG	1	704x480	1-way	1/1	-	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

StarDot										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SD-130	v1.1.61	M-JPEG	1	1296x960	-	-	-	-	-	
SD-300		M-JPEG	1	2048x1536	-	-	-	-	-	Supported by design
SD-500	v1.1.61	M-JPEG	1	2592x1944	-	-	-	-	-	
SDEXP4	v1.1.61	M-JPEG	4	704 x 416	-	-	-	-	-	
SDEXP2	v1.1.61	M-JPEG	2	704 x 416	-	-	-	-	-	
SDH130B		H.264 M-JPEG	1	1296 x 976	-	1/0	-	-	-	Supported by design
SDH130BN		H.264 M-JPEG	1	1296 x 976	-	1/0	-	-	-	Supported by design
SDH130V		H.264 M-JPEG	1	1296 x 960	-	1/0	-	-	-	Supported by design
SDH130VN		H.264 M-JPEG	1	1296 x 960	-	1/0	-	-	-	Supported by design
SDH300B		H.264 M-JPEG	1	2048 x 1536	-	1/0	-	-	-	Supported by design
SDH300V		H.264 M-JPEG	1	2048 x 1536	-	1/0	-	-	-	Supported by design
SDH500B		H.264 M-JPEG	1	2560 x 1944	-	1/0	-	-	-	Supported by design
SDH500BN	v1.1.68	H.264 M-JPEG	1	2560 x 1944	-	1/0	-	-	-	
SDH500V		H.264 M-JPEG	1	2592 x 1944	-	1/0	-	-	-	Supported by design
SDH500VN		H.264 M-JPEG	1	2592 x 1944	-	1/0	-	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Sony										
SONY										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SNC-CM120	1	MPEG4 M-JPEG	1	1280x960	2-way	1/2	Yes	-	-	
SNC-CS10		MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	-	Supported by design
SNC-CS11	1.05	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	-	
SNC-CS20	1	MPEG4 M-JPEG	1	768x576	2-way	1/2	-	-	-	
SNC-CS3		M-JPEG	1	736x480	-	1/2	-	-	-	Supported by design
SNC-CS50	2.21	MPEG4 M-JPEG	1	640x480	2-way	2/2	-	-	-	
SNC-DF40	1.17	MPEG4 M-JPEG	1	640x480	2-way	1/2	-	-	-	
SNC-DF50	1.11	H.264 MPEG4 M-JPEG	1	640x480	2-way	1/2	-	-	-	
SNC-DF70	1.17	MPEG4 M-JPEG	1	640x480	2-way	1/2	-	-	-	
SNC-DF80	1.11	H.264 MPEG4 M-JPEG	1	640x480	2-way	1/2	Yes	-	-	
SNC-DF85	0.9	H.264 MPEG4 M-JPEG	1	640x480	2-way	1/2	-	-	-	
SNC-DM110		MPEG4 M-JPEG	1	1280x960	2-way	1/2	-	-	-	Supported by design
SNC-DM160	1.01	MPEG4 M-JPEG	1	1280x960	2-way	1/2	Yes	-	-	
SNC-DS10	1.01	H.264 MPEG4 M-JPEG	1	768x576	2-way	1/2	-	-	-	
SNC-DS60	1	MPEG4 M-JPEG	1	640x480	2-way	1/2	-	-	-	
SNC-P1	1.28	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	-	
SNC-P5	1.28	MPEG4 M-JPEG	1	640x480	2-way	2/1	Yes	-	-	
SNC-RX530	3.03	H.264 MPEG4 M-JPEG	1	640x480	2-way	2/2	Yes	-	-	
SNC-RX550	2.21	H.264 MPEG4 M-JPEG	1	640x480	2-way	2/2	Yes	-	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Sony										
SONY										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SNC-RX570	3.01	H.264 MPEG4 M-JPEG	1	640x480	2-way	2/2	Yes	-	-	
SNC-RZ25	1.29	MPEG4 M-JPEG	1	640x480	2-way	2/2	Yes	-	-	
SNC-RZ30	3.14	M-JPEG	1	736x480	-	3/2	Yes	-	-	
SNC-RZ50	2.21	H.264 MPEG4 M-JPEG	1	640x480	2-way	2/2	Yes	-	-	
SNC-Z20	1.06	M-JPEG	1	736x480	-	1/2	Yes	-	-	
Note:	PTZ Support: zoom only.									
SNT-V704	2.15	MPEG4 M-JPEG	4	720x480	2-way	1/4	-	-	-	
SNT-EX104	1.10.01	H.264 MPEG4 M-JPEG	4	720x576(PAL) 720x480(NTSC)	2-way	4/4	Yes	Yes	-	
SNC-DH180	1.10.02	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/2	-	-	-	
SNC-RH124	1.10.01	H.264 MPEG4 M-JPEG	1	1280x720	2-way	4/2	Yes	-	-	
SNC-CH140	1.07.00	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/2	-	Yes	-	
SNC-CH180	1.10.03	H.264 MPEG4 M-JPEG	1	1280x720	2-way	1/2	-	Yes	-	
SNC-CH240	1.10.01	H.264 MPEG4 M-JPEG	1	1680x1056	2-way	1/2	Yes	Yes	-	
Note:	Do not support 1920x1440/1920x1080 resolution									
SNC-DH140	1.07.00	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/2	-	Yes	-	
SNC-DH240	1.10.02	H.264 MPEG4 M-JPEG	1	1680x1056	2-way	1/2	-	Yes	-	
Note:	Do not support 1920x1440/1920x1080 resolution									
SNC-RH164	1.10.01	H.264 MPEG4 M-JPEG	1	1280x720	2-way	4/2	Yes	Yes	-	
SNC-RS46P	1.10.02	H.264 MPEG4 M-JPEG	1	720x576	2-way	4/2	Yes	Yes	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Sony

SONY

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SNT-EX154	1.10.01	H.264 MPEG4 M-JPEG	4	720x480	2-way	4/4	Yes	Yes	-	
SNT-EX101E	1.10.01	H.264 MPEG4 M-JPEG	1	720x480	2-way	2/2	Yes	Yes	-	
SNT-EP154	1.10.01	H.264 MPEG4 M-JPEG	4	720x480	-	-	-	Yes	-	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Toshiba

TOSHIBA

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IKWB02A		M-JPEG	1	640x480	2-way	-	-	-	-	Supported by design
IKWB15A		M-JPEG	1	1280x960	2-way	-	Yes	-	-	Supported by design
IKWB21A	2.09.E.103.121	M-JPEG	1	1280x960	2-way	-	Yes	-	-	
IKWB70A	0100e	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	-	Yes	
IKWD01A	0100a	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	-	Yes	
IKWR01A		M-JPEG	1	640x480	2-way	-	-	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

TRUEN


TRUEN

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
TCS-200	T122	H.264	1	720x576	1-way	2/2	Yes	-	-	
TCAM-230		H.264	1	720x576	1-way	1/1	Yes	-	-	Supported by design
TCAM-250		H.264	1	720x576	1-way	1/1	Yes	-	-	Supported by design
TCAM-251	V1.T122	H.264	1	720x576	1-way	1/1	Yes	-	-	
TCAM-270L	V1.108F	H.264	1	720x576	1-way	1/1	Yes	-	-	
TCAM-270M		H.264	1	720x576	1-way	1/1	Yes	-	-	Supported by design
TCAM-270H		H.264	1	720x576	1-way	1/1	Yes	-	-	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

VIVOTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
FD61x1		MPEG4 M-JPEG	1	720x480	2-way	1/1	-	-	Yes	Supported by design
FD61x2		MPEG4 M-JPEG	1	720x480	2-way	1/1	-	-	Yes	Supported by design
FD7130	0100e	MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	
FD7131		MPEG4 M-JPEG	1	720x480	2-way	1/1	-	-	Yes	Supported by design
FD7132	0100f	MPEG4 M-JPEG	1	640x480	-	1/1	-	-	Yes	
FD7141	0100g	MPEG4 M-JPEG	1	720x480	-	1/1	-	-	Yes	
Note:	MPEG4: Unable to connect through HTTP.									
FD7160		MPEG4 M-JPEG	1	1600x1200	-	-	-	-	Yes	Supported by design
IP21x1		M-JPEG	1	720x576	-	1/1	-	-	Yes	Supported by design
IP21x2		M-JPEG	1	720x576	1-way	1/1	-	-	Yes	Supported by design
IP3132		H.263	1	720x576	1-way	1/1	-	-	Yes	Supported by design
IP3133		H.263	1	720x576	1-way	1/1	-	-	Yes	Supported by design
IP3135		H.263	1	720x576	1-way	-	-	-	Yes	Supported by design
IP3135-PLNK		H.263	1	720x576	1-way	1/2	-	-	Yes	Supported by design
IP3136		H.263	1	720x576	1-way	-	-	-	Yes	Supported by design
IP3136-PLNK		H.263	1	720x576	1-way	1/2	-	-	Yes	Supported by design
IP3137		H.263	1	720x576	1-way	1/1	-	-	Yes	Supported by design
IP31x1	0201b	H.263	1	720x576	-	1/1	-	-	Yes	
IP31x1TLFN		H.263	1	720x576	-	1/1	-	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List


V 1.4.0 (2010.08.09)

VIVOTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IP31x2		H.263	1	720x576	1-way	1/1	-	-	Yes	Supported by design
IP31x7		H.263	1	720x576	1-way	1/1	-	-	Yes	Supported by design
IP51x2		MPEG4	1	720x576	2-way	1/1	-	-	Yes	Supported by design
IP51x4		MPEG4	1	720x576	2-way	1/1	-	-	Yes	Supported by design
IP6114		MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	Supported by design
IP6124		MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	Supported by design
IP61x2		MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	Supported by design
IP61x4		MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	Supported by design
IP61x7		MPEG4 M-JPEG	1	720x576	2-way	1/1	-	-	Yes	Supported by design
IP7130	0100c	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
IP7131		MPEG4	1	704x576	1-way	1/1	-	-	Yes	Supported by design
IP7132		MPEG4	1	704x576	1-way	1/1	-	-	Yes	Supported by design
IP7133	0100b	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
IP7134	0100b	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
IP7135		MPEG4	1	704x576	1-way	-	-	-	Yes	Supported by design
IP7137		MPEG4	1	704x576	1-way	-	-	-	Yes	Supported by design
IP7138	0101h	MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	
IP7139		MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	-	Yes	Supported by design
IP7142		MPEG4 M-JPEG	1	704x576	2-way	1/1	-	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

VIVOTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IP7151		MPEG4 M-JPEG	1	704x576	2-way	1/1	-	-	Yes	Supported by design
IP7152		MPEG4 M-JPEG	1	704x576	2-way	1/1	-	-	Yes	Supported by design
IP7153	0100g	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	-	Yes	
IP7154	0100b	MPEG4 M-JPEG	1	640x480	2-way	1/1	Yes	-	Yes	
IP7160	0101b	MPEG4 M-JPEG	1	1600x1200	2-way	1/1	-	-	Yes	
IP7161		MPEG4 M-JPEG	1	1600x1200	2-way	1/1	-	-	Yes	Supported by design
IP71x7		MPEG4	1	704x576	1-way	1/1	-	-	Yes	Supported by design
IP7251	0100f	MPEG4	1	640x480	2-way	1/1	Yes	-	Yes	
Note:	MPEG4: Unable to connect through HTTP.									
IP7330		MPEG4 M-JPEG	1	640x480	-	1/0	-	-	Yes	Supported by design
IP7361		MPEG4 M-JPEG	1	1600x1200	2-way	1/1	-	-	Yes	Supported by design
IZ7151		MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	Supported by design
Note:	PTZ Support: zoom only.									
PT3134		H.263	1	720x576	1-way	1/1	Yes	-	Yes	Supported by design
PT31x2		H.263	1	720x576	1-way	1/1	Yes	-	Yes	Supported by design
PT31x3		H.263	1	720x576	1-way	1/1	Yes	-	Yes	Supported by design
PT31x4		H.263	1	720x576	1-way	1/1	Yes	-	Yes	Supported by design
PT31x7		H.263	1	720x576	1-way	1/1	Yes	-	Yes	Supported by design
PT7000		MPEG4	1	720x576	1-way	-	Yes	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List


V 1.4.0 (2010.08.09)

VIVOTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
PT7135		MPEG4	1	720x576	1-way	-	Yes	-	Yes	Supported by design
PT7137		MPEG4	1	704x576	1-way	-	Yes	-	Yes	Supported by design
PZ61x2	0105e	MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	
PZ61x4		MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	Supported by design
PZ7131	0100b	MPEG4 M-JPEG	1	640x480	2-way	1/1	Yes	-	Yes	
PZ7151	0101b	MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	
Note:	MPEG4: Unable to connect through HTTP.									
PZ7152		MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	Supported by design
PZ71X1		MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	Supported by design
PZ71X2		MPEG4 M-JPEG	1	704x576	2-way	1/1	Yes	-	Yes	Supported by design
SD61x2		MPEG4 M-JPEG	1	720x576	2-way	4/1	Yes	-	Yes	Supported by design
SD7151	0101d	MPEG4 M-JPEG	1	720x576	2-way	4/1	Yes	-	Yes	
Note:	No audio support in M-JPEG format.									
Note:	MPEG4: Unable to connect through HTTP.									
SD73X3	0100h	MPEG4 M-JPEG	1	704x576	2-way	4/1	Yes	-	Yes	
TC5330		MPEG4 M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
TC5331		MPEG4	1	720x576	1-way	-	-	-	Yes	Supported by design
Note:	MPEG4: Unable to connect through HTTP.									
VS2101		M-JPEG	1	720x576	-	1/1	-	-	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

VIVOTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
VS2401		M-JPEG	4	720x576	-	4/2	-	-	Yes	Supported by design
VS2402		M-JPEG	4	720x576	-	4/2	-	-	Yes	Supported by design
VS2403	0103b	M-JPEG	4	720x576	1-way	4/4	Yes	-	Yes	
VS3100		H.263	1	720x576	1-way	1/1	-	-	Yes	Supported by design
VS3101		H.263	1	720x576	-	1/1	-	-	Yes	Supported by design
VS3102		H.263	1	720x576	1-way	1/1	-	-	Yes	Supported by design
VS3102-XLTH		H.263	1	720x576	1-way	1/1	-	-	Yes	Supported by design
VS7100	0101e	MPEG4 M-JPEG	1	720x576	-	1/1	Yes	-	Yes	
Note:	MPEG4: Unable to connect through HTTP.									
Note:	Audio: All cameras don't support AAC audio codec, but GSM-AMR.									
IP8161	0101b	MPEG4 M-JPEG H.264	1	1600x1200	2-way	1/1	Yes	-	Yes	
Note:	PTZ only support zoom in/out									
VS8102	0100f	MPEG4 M-JPEG H.264	1	1600x1200	2-way	1/1	-	-	Yes	
FD8161	0100g	MPEG4 M-JPEG H.264	1	1600x1200	2-way	1/1	-	-	Yes	
FD8361	0100d1	MPEG4 M-JPEG H.264	1	1600x1200	2-way	1/1	-	-	Yes	
Note:	MPEG4: Unable to connect through HTTP.									
Note:	Audio: All cameras don't support AAC audio codec, but GSM-AMR.									

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Y-cam



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
Black	V3.25B	MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	
White	V3.25B	MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	
Knight	V3.25B	MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Zavio										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
B5110	MG.0.6.01_C1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	Yes	Supported by design
B6110	MG.0.6.01_C1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	Yes	Supported by design
D510E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design
D520E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design
D610A	LM.1.6.16	MPEG4 M-JPEG	1	640x480	2-way	-	-	Yes	Yes	Testing by manufactor
D6111	MG.0.6.01_C1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	Yes	Supported by design
D611E	LM.1.6.16	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Testing by manufactor
F210A	LM.1.6.15	MPEG4 M-JPEG	1	640x480	2-way	-	-	Yes	Yes	Testing by manufactor
F3100	MG.0.6.01_C1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	-	-	Yes	Yes	Supported by design
F3105	MG.0.6.01_C1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	-	-	Yes	Yes	Supported by design
F312A	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	-	-	Yes	Yes	Supported by design
F5100	MG.0.6.01_C1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	Yes	Supported by design
F5105	MG.0.6.01_C1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	Yes	Supported by design
F510E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design
F510W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design
F5110	MG.0.6.01_C1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	Yes	Supported by design
F5115	MG.0.6.01_C1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	Yes	Supported by design
F511E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design
F511W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO

IP+ Supported Camera List

V 1.4.0 (2010.08.09)

Zavio



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
F520E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design
F521E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design
F531E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design
F610A	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design
F611E	LM.1.6.16.00 7	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Testing by manufactor
F721A	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	-	-	Yes	Yes	Supported by design
F731E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	-	Yes	Yes	Supported by design
M510E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	Yes	Yes	Yes	Supported by design
M510W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	Yes	Yes	Yes	Supported by design
M511E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	Yes	Yes	Yes	Supported by design
M511W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	Yes	Yes	Yes	Supported by design
P5110	MG.0.5.0.1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	Yes	Yes	Yes	Testing by manufactor
P5115	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	Yes	Yes	Yes	Testing by manufactor
V111T	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	2-way	1/1	Yes	Yes	Yes	Supported by design

Remarks: Supported by Design means that camera model shares the same API of an existing tested camera, but has not been tested or validated by NUUO